

**OLIEHANDEL KLAAS DE BOER B.V.**

Trawlerkade 58
1976 CB IJMUIDEN
+31-(0)255-513240
bunkers@klaasdeboer.nl

ISO 8217 2010 Fuel Standard for Distillate Marine Fuels DMA 0,860

Characteristics	Unit	Limit	Result
Viscosity @ 40°C	mm ² /s	Max.	6.000
Viscosity @ 40°C	mm ² /s	Min.	1.500
Density @ 15°C	kg/m ³	Max.	860.0
Cetane index	-	Min.	40
Sulphur	mass %	Max.	0.1%
Flash Point	°C	Min.	60
Hydrogene Sulfide	mg/kg	Max.	2.00
Acid number	mg KOH/g	Max.	0.5
Oxidation stability	g/m ³	Max.	25
Micro Carbon residue at 10% residue	mass %	Max.	0.3
Pour Point (upper) (b) (Summer)	°C	Max.	0
Pour Point (upper) (b) (Winter)	°C	Max.	-6
Cloud Point	°C	Max.	-
Water	volume %	Max.	-
Ash	Mass %	Max.	0.01
Lubricity, corrected wear scar diameter (wsd 1.4) @ 60°C	µm	Max.	520
Appearance			Clear & Bright
FAME content	% v/v	Max.	0.5

The above is for informational purposes only. Oliehandel Klaas de Boer B.V. assumes no responsibility for any errors or omissions.